

FIBRE CABLE CIRCUIT

Cct_No: F3309 WAN Tx CCC to EROF

Function: IT services

Cable No	Cable	Core	Colour	Tube	Length (m)	Adaptors		Status
300.2	[CCC] - [CCC_GF] [12cUG] [3020]	7	BL	OR	0	CCC - FIST C5 07	CCC_GF - SPG - 07	E
302.13	[P3126] - [CCC] [48UGc] [302]	37	SL	GY	269	-	CCC - FIST G4 37	E
302.12	[P3125] - [P3126] [48UGc] [302]	37	SL	GY	280	-	-	E
302.11	[P3124A] - [P3125] [48SSb] [302]	37	SL	GY	231	-	-	E
302.09	[P3124] - [P3124A] [48SSb] [302]	37	SL	GY	651	-	-	E
302.08	[P3123C] - [P3124] [48SSb] [302]	37	SL	GY	577	-	-	E
302.07	[P3123B] - [P3123C] [48SSb] [302]	37	SL	GY	602	-	-	E
302.06	[P3123A] - [P3123B] [48SSb] [302]	37	SL	GY	479	-	-	E
302.05	[P3123] - [P3123A] [48SSb] [302]	37	SL	GY	744	-	-	E
302.04	[P3122B] - [P3123] [48SSb] [302]	37	SL	GY	840	-	-	E
302.03	[P3122A] - [P3122B] [48UGc] [302]	37	SL	GY	476	-	-	E
302.02	[P3122] - [P3122A] [48UGc] [302]	37	SL	GY	166	-	-	E
302.01	[HERS] - [P3122] [48SSb] [302]	37	SL	GY	162	HERS - FIST H4 37	-	E
307.06	[P3121A] - [HERS] [48UGa] [307]	31	BL	WH	140	-	HERS - FIST G3 31	E
307.05	[P3121] - [P3121A] [48UGa] [307]	31	BL	WH	206	-	-	E
307.04	[P3120] - [P3121] [36UGa] [307]	31	BL	WH	260	-	-	E
307.03	[P3119] - [P3120] [36UGa] [307]	31	BL	WH	223	-	-	E
307.71	[P3119] - [P3130] [36UGb] [307]	1	BL	BL	250	-	-	E
307.72	[P3130] - [EROF] [36UGb] [307]	1	BL	BL	65	-	EROF - OTP - 01	E
Splices: 22 Connectors: 6		Circuit Total length:			6621			

Attenuation Estimate at 1310nm Minimum 3.60 dB Maximum 6.82 dB